

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 774 926 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention
of the grant of the patent:
09.06.1999 Bulletin 1999/23

(21) Application number: **94922673.2**

(22) Date of filing: **25.07.1994**

(51) Int. Cl.⁶: **A61B 17/39**

(86) International application number:
PCT/US94/08251

(87) International publication number:
WO 95/05781 (02.03.1995 Gazette 1995/10)

(54) **R-F ABLATION APPARATUS**

GERAET ZUR RADIOFREQUENZABLATION
APPAREIL D'ABLATION A RADIOFREQUENCE

(84) Designated Contracting States:
DE FR GB IT NL SE

(30) Priority: **27.08.1993 US 113441**

(43) Date of publication of application:
28.05.1997 Bulletin 1997/22

(73) Proprietor: **MEDTRONIC, INC.**
Minneapolis, Minnesota 55432-3576 (US)

(72) Inventors:
• **MULIER, Peter, M., J.**
St. Paul, MN 55112 (US)

• **HOEY, Michael, F.**
Shoreview, MN 55126 (US)

(74) Representative:
Hughes, Andrea Michelle
Frank B. Dehn & Co.,
European Patent Attorneys,
179 Queen Victoria Street
London EC4V 4EL (GB)

(56) References cited:
EP-A- 0 013 605 **DE-C- 651 428**
FR-A- 1 454 773 **US-A- 4 524 770**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 774 926 B1

Description

[0001] This invention relates generally to the field of devices for cardiac surgery, and more specifically to devices for R-F ablation of cardiac tissue.

[0002] The present invention is directed toward treatment of tachyarrhythmias, which are heart rhythms in which a chamber or chamber of the heart exhibits an excessively fast rhythm. In particular, the present invention is directed toward treatment of tachycardias, which are due to the presence of ectopic foci within the cardiac tissue or due to the presence of aberrant conduction pathways within the cardiac tissue.

[0003] Therapies have been developed for treating tachycardias by destroying cardiac tissue containing identified ectopic foci or aberrant conduction pathways. A variety of approaches have been taken, including application of electrical energy or other forms of energy to destroy the undesired cardiac tissue. As examples, ablation of cardiac tissue has been accomplished by means of radio frequency electrical current, microwave energy, heat, electrical pulses, cryotherapy, and lasers. At present, ablation using R-F energy is perhaps the most widely practised in the context of ablation procedures that can be carried out by means of a catheter, inserted into the closed heart.

[0004] Most R-F ablation catheters employ electrodes which are intended to contact the endocardium of the heart, or, in some cases as in U.S. Patent No. 5,083,565, issued to Parins, are intended to penetrate the endocardium, and enter the myocardium. In general, R-F ablation catheters are effective to induce small lesions in heart tissue including the endocardium and inner layers of myocardium, in the immediate vicinity of the electrode. However, the medical community has expressed a desire for devices which produce larger lesions, to reduce the number of applications of R-F energy (burns) required to effectively ablate the cardiac tissue associated with the tachycardia.

[0005] R-F ablation causes tissue in contact with the electrode to heat, through resistance of the tissue to the induced electrical current therethrough. The actual extent of heating is somewhat unpredictable. However, temperature tends to rise as the duration and amplitude of the R-F signal increase. Heating of the tissue beyond a certain point can cause dissection or charring of the tissue, resulting in a high impedance between the R-F electrode and the return electrode, which in turn leads to cessation of the heating process, and, in some cases, sticking of the electrode to the charred tissue. One response to this phenomenon has been the inclusion of thermocouple within the ablation electrode, in conjunction with feedback control to modulate the R-F signal to maintain the electrode temperature at a set parameter. One such system is disclosed in U.S. Patent No. 5,122,137 to Lennox et al.

[0006] US-A-4 524 770 discloses a hollow needle for attachment to an endoscopic instrument or catheter.

[0007] EP-A-0 013 605 discloses a stylet insertion assembly for a body implantable lead.

[0008] According to one aspect of the present invention, there is provided an ablation catheter system, comprising:

an elongate catheter body having a proximal portion, a distal portion and a longitudinal lumen;
a hollow needle for penetrating body tissue at a desired location, mounted to a distal portion of said catheter body and having an internal lumen coupled to the lumen of said catheter body; and
a source of conductive fluid, coupled to the internal lumen of said catheter body, for delivering a conductive fluid to said lumen of said catheter body; characterised by
a conductive electrode surface for delivering R-F energy to said desired location, mounted to said distal portion of said catheter body; and
a source of R-F electrical energy, coupled to said electrode surface, and wherein
said hollow needle is a helical needle.

[0009] According to another aspect, there is provided an ablation catheter comprising:

an elongate catheter body having a proximal portion, a distal portion and a longitudinal lumen;
a hollow needle for penetrating body tissue at a desired location, mounted to a distal portion of said catheter body and having an internal lumen coupled to the lumen of said catheter body; and
means for coupling the internal lumen of the catheter body to a source of conductive fluid, for delivering a conductive fluid to said lumen of the catheter body, characterised by
a conductive electrode surface for delivering R-F energy to said desired location, mounted to said distal portion of said catheter body; and
means for coupling a source of R-F electrical energy to said electrode surface, and wherein
said hollow needle is a helical needle.

[0010] The present invention is directed toward improving the consistency and efficacy of R-F ablation, and to increase the overall size and extent of the lesions induced by R-F ablation. These goals are pursued by means of an ablation catheter employing a helical electrode intended to be screwed into the myocardium at the site intended for ablation. The helical electrode provides an enlarged surface area as compared to relatively straight or needle-like electrodes for insertion into the endocardium, and also serves to stabilize the location of the catheter during the application of the R-F signal. In addition, there is essentially no bleeding following removal of the helical electrode, so it can safely be placed in multiple locations for mapping and ablation purposes.

[0011] An additional aspect of the invention in its preferred embodiment is the provision of a non-toxic, non-arrhythmogenic, conductive solution such as Ringer's solution to the area of the electrode, before and during application of R-F energy. In the preferred embodiment, the conductive solution is applied through one or more apertures in the electrode. The conductive solution injected prior to application of the R-F signal is believed to displace blood in the vicinity of the electrode. Ringer's solution, for example, has a much higher conductivity than blood (approximately 3-4x) or cardiac muscle (approximately 7x), overall resistance to the induced electrical current is reduced, which is believed to assist in expanding the size of the lesion, by spreading the effective area of application of the electrical current over a wider area. Application of the conductive solution during the burn further assists by preventing overheating of the tissue, allowing for a prolonged application of the R-F signal, extending beyond the point at which burning or charring would otherwise normally occur. Both of these factors are believed to contribute to an increase in the overall size of the lesion produced by application of R-F energy at a particular location.

[0012] Preferred embodiments will now be described, by way of example only, with reference to the accompanying drawings.

Figure 1 is a plan view of a catheter adapted to perform an improved method of R-F ablation, in accordance with the present invention.

Figure 2 is a cutaway view through the distal end of the catheter illustrated in Figure 1.

Figures 3, 4, and 5 illustrate alternative embodiments of the helical electrode of the catheter illustrated in Figures 1 and 2.

Figure 6 illustrates associated apparatus for administration of conductive solution before and during application of R-F energy to the helical electrode.

[0013] Figure 1 is a plan view of a catheter specifically designed for performing R-F ablation according to the present invention. The catheter includes an elongated catheter body 10, comprising an insulative outer sheath 12, which may be made of polyurethane, Teflon®, or other biocompatible plastic. A hollow, helical electrode 14 is located at the distal end of the catheter and is coupled to the distal end of an internal tube, running the length of the catheter. At the proximal end of the catheter a fitting 16 is located, to which luer lock 18 is coupled. Luer lock 18 is coupled to the proximal end of the internal tube. A swivel mount 20 is mounted to luer lock 18, allowing rotation of the catheter relative to luer lock 22. Luer lock 22 is intended to be coupled to a source of conductive fluid such as Ringer's solution, and allows for application of the Ringer's solution through the catheter and through electrode 14, while electrode 14 is being screwed into heart tissue. An electrical connector 24 exits fitting 16, and is coupled to electrode 14, allow-

ing for the use of electrode 14 to apply R-F energy to heart tissue. Electrode 14 may also be employed for other related functions such as measurement of electrograms within the heart and pacing of heart tissue by application of low energy pulses appropriate for cardiac pacing. In use, the catheter is advanced to the desired site for ablation, which preferably has been previously identified by means of cardiac mapping in a fashion similar to cardiac mapping presently employed with R-F ablation procedures. The catheter may be guided to the desired location by being passed down a steerable or guidable catheter, for example, as disclosed in U.S. Patent No. 5,030,204, issued to Badger et al., or by means of a fixed configuration guide catheter, for example in U.S. Patent No. 5,104,393, issued to Isner. Alternatively, the catheter may be advanced to the desired site within a heart by means of a deflectable stylet, as disclosed in PCT Patent Application WO 93/04724, published March 18, 1993, or a deflectable guidewire as disclosed in U.S. Patent No. 5,060,660, issued to Gambale, et al. When the hollow needle 14 is located at the desired location it is screwed into heart tissue by rotating the catheter body. A torque cable within the catheter body provides for 1:1 torque transfer from the proximal end of the catheter to the hollow needle 14.

[0014] When advanced to the desired location, luer lock 22 is coupled to a pressurized source of Ringer's solution. An appropriate source is discussed in more detail in conjunction with Figure 6 below. However, for purposes of the present invention, a source of Ringer's solution capable of delivering 1 cc per minute of solution at atmospheric pressure has been found to be adequate. Delivery of Ringer's solution should begin before or at the time at which the electrode 14 is screwed into the tissue to be ablated. In animal experimentation, the inventors have found that delivery of Ringer's solution for a period of two minutes prior to the delivery of R-F energy assists in producing a larger but still controlled, regular lesion.

[0015] After the electrode has been located, and Ringer's solution has been administered for the desired period of time, electrical connector 24 is coupled to an R-F electrosurgical power source, of the type commercially available and employed for cutting an electrocoagulation. The present inventors have employed a Blendtome brand electrosurgical generator, Model No. 755, coagulation setting number 7, cutting setting number 1. At these settings, a prolonged application of R-F energy, e.g., one minute or so, may be employed to produce a large, controlled lesion. Greater or lesser time periods may be employed, however, time periods less than 20 seconds may be counter-indicated, as it appears that the cooling effect of the Ringer's solution, in such shorter R-F application times, may actually decrease the effective size of the lesion.

[0016] After R-F ablation, the electrode 14 may be coupled to a cardiac pacemaker, and cardiac pacing energy may be delivered to the lesion site in an attempt

to measure the pacing threshold. Pacing threshold may be measured by delivering pacing pulses at differing energy levels, e.g. by altering pulse amplitude or width, and determining the minimum energy level effective to cause a depolarization of cardiac tissue. The inventors believe that the higher the pacing threshold, assuming a relatively homogenous lesion, the greater lesion size. As such, the electrode 14 can be used to derive a rough estimate of overall lesion size. The electrode 14 may also be coupled to EKG monitoring equipment to assist in determining whether the tachycardia persists and whether the tissue in the vicinity of the electrode is still participating in aberrant conduction or ectopic activity, associated with the tachycardia.

[0017] The helical configuration of electrode 14 is believed to be particularly beneficial in the context of an ablation electrode. Because the electrode is screwed into and completely located within the heart tissue, out of the bloodstream, application of R-F energy is limited to the tissue itself. This differs from traditional R-F ablation electrodes, which simply contact the endocardium, with the result that a substantial portion of the energy applied is dissipated in the blood within the heart adjacent the electrode site. Moreover, R-F energy applied to the bloodstream may cause clotting of the blood adjacent the electrode, and raise the risk of clots breaking loose of the electrode.

[0018] The helical electrode also provides a substantially increased surface area as compared to the needle-like electrodes proposed in the above cited Parins patent, and also serves to anchor the catheter reliably during application of the R-F energy. In addition, the helical shape of the electrode prevents the application of conductive solution through the electrode from causing the electrode to be backed out of its insertion site due to hydraulic pressure, as might occur if a straight, hollow electrode were employed. The elongate path defined by the helical electrode also reduces the possibility of leakage of conductive fluid along the needle and out of the heart tissue. -

[0019] Figure 2 illustrates a cutaway version through the end of the catheter illustrated in Figure 1. In this view, it can be seen that helical electrode 14 is provided with an internal lumen 26 which is in communication with the internal lumen of a tube 30. Tube 30 extends to the proximal end of the catheter and is in full communication with luer lock 18, as discussed above. Tube 30 may be fabricated of polyimide tubing or of stainless steel tubing. In the present invention, the stainless steel tubing serves as an additional conductor, coupling electrode 14 to electrical connector 24 and enhancing the overall conductivity of the catheter. The use of polyimide tubing, while reducing the overall conductivity of the catheter enhances the flexibility somewhat, and may be beneficial in some cases. It is recommended to apply a steady flow of Ringer's solution through the tubing to electrode 14 during passage of the catheter through the vascular system to the electrode site, if possible. The

flow of Ringer's solution in this case assists in maintaining the patency of the lumen of tubing 30, and prevents plugging of the exit ports of the electrode as it is advanced into the cardiac muscle.

[0020] Surrounding tube 30 are two coils 32 and 34, which are wound in opposite directions, to provide a torque cable. In the case of the specific devices employed by the inventors, a torque cable as manufactured by Lake Region Manufacturing Company of Chaska, Minnesota was employed, which torque cable is described in U.S. Patent No. 5,165,421. Coils 32 and 34 also serve as conductors. As illustrated, tubing 30 is between metal coils 32 and 34 and helical electrode 14. However, if polyimide tubing is used, the coils 32 and 34 will serve as the only conductor and thus will be electrically coupled to electrode 14 by means of welding, soldering or mechanical interconnection. Insulative sleeve 12 serves both to provide a smooth exterior for the catheter and to insulate the metal coils 32 and 34, along the length of the catheter.

[0021] Figures 3, 4 and 5 illustrate alternative embodiments of the helical electrode illustrated in Figure 2. The electrode in Figure 2 comprises a hollow tube having a single exit port located as its distal end. Electrode 36, illustrated in Figure 3, corresponds to electrode 14 with the exception that additional exit ports 38, 40 and 42 have been added, allowing for dispensing of the Ringer's solution along the length of the helix. Ports 38, 40 and 42 may be laser drilled, and may be spaced in any desired fashion around the circumference of electrode 36 and along the length of electrode 36. Preferably, it is believed desirable to have ports spaced around the full circumference of the electrode, to provide for an even dispensing and dispersing of Ringer's solution.

[0022] Electrode 44, illustrated in Figure 4 is a second alternative embodiment of a helical electrode corresponding to electrode 14, but with the addition of an insulative sleeve 46, which covers the proximal portion of the electrode. Sleeve 46 limits the application of R-F energy to the distal portion of the electrode. Optionally, additional exit ports corresponding to ports 38, 40 and 42 illustrated in Figure 43 may also be employed in conjunction with electrode 44. These additional exit ports may be limited to the exposed, uninsulated portion of electrode 44, or may extend along the entire length of electrode 44.

[0023] Electrode 48, illustrated in Figure 5 is a third alternative embodiment corresponding generally to electrode 14. However, in this case, electrode 48 is provided with a thermocouple 50 located in the distal end of electrode 48. Thermocouple wires 52 and 54 extend backwards through the lumen within electrode 48 and are used to monitor the temperature at the tip of the electrode, for use in feedback control of power applied to the electrode as described in the above-cited patent issued to Lennox et al. Only one of thermocouple wires 54 and 52 is insulated, and the other is simply coupled to the interior of electrode 48. In order to employ the

electrode of Figure 4B, an additional electrical connector would have to be added to the embodiment illustrated in Figure 5, in order to allow connection to the thermocouple wire not connected to electrode 48. Alternatively, both thermocouple wires may be insulated, requiring two additional electrical connectors at the proximal end of the device, each coupled to one of the thermocouple wires. It should be noted that the thermocouple 50 effectively blocks the distal opening of the lumen within electrode 48, so that Ringer's solution will be dispensed only by means of side ports 56, 58 and 60.

[0024] Figure 6 illustrates a pressurized source for Ringer's solution which may be employed in conjunction with the catheter illustrated in Figure 1. A reservoir 100 is provided, which is commercially manufactured by Block Medical Inc., and sold under the brand name "Home Pump". The reservoir contains Ringer's solution and provides Ringer's solution at one atmosphere pressure to flow control 102, via filter 104. Flow control 102 may, for example, provide a flow limit of 20 drops or 1 cc per minute. Flow control 102 is coupled to a second flow control element 104, which, in the experimental apparatus employed by the inventors allows for additional adjustability of flow rates. Flow control 104 is coupled to the luer lock 22, illustrated in Figure 1, which in turn is in fluid communication with electrode 14 (Figure 1), allowing delivery of Ringer's solution to the electrode. An electrosurgical generator 200 for providing R-F electrical energy is illustrated in functional block form, coupled to electrical connector 24 and to a ground plate electrode 202 (not drawn to scale). All other labelled elements correspond to those illustrated in Figure 1.

[0025] While the embodiment illustrated above requires a second element (e.g. a guide catheter or guide wire) for advancing and positioning the catheter at its desired location, it is anticipated that the basic apparatus disclosed above may also be incorporated into catheters which themselves are steerable or deflectable, similar to R-F ablation catheters presently in clinical investigation. Similarly, it is anticipated that in commercial embodiments, alternative mechanisms (e.g. precision pumps) for controlling the flow of Ringer's solution may be employed. Similarly, while the inventors have employed Ringer's solution, other alternative fluids may be workable as well. As such, the embodiment discussed above should be considered exemplary, rather than limiting, in conjunction with the following claims.

Claims

1. An ablation catheter system, comprising:

an elongate catheter body (10) having a proximal portion, a distal portion and a longitudinal lumen;
a hollow needle (14) for penetrating body tissue at a desired location, mounted to a distal por-

tion of said catheter body (10) and having an internal lumen coupled to the lumen of said catheter body (10); and

a source of conductive fluid, coupled to the internal lumen of said catheter body, for delivering a conductive fluid to said lumen of said catheter body (10); characterised by
a conductive electrode surface (14) for delivering R-F energy to said desired location, mounted to said distal portion of said catheter body (10); and
a source of R-F electrical energy, coupled to said electrode surface (14), and wherein said hollow needle is a helical needle.

2. A catheter system according to claim 1 wherein said hollow needle is conductive and wherein said electrode surface comprises a surface of said hollow needle.
3. A catheter system according to claim 1 or claim 2, wherein said fluid delivery means comprises means for delivering Ringer's solution.
4. A catheter system according to any preceding claim wherein said conductive fluid delivery means comprises a reservoir containing said conductive fluid and a means for controlling fluid flow.
5. A catheter system according to any preceding claim, wherein said catheter body comprises a torque transfer cable, extending longitudinally along said catheter body.
6. A catheter system according to claim 5 wherein said torque transfer cable is conductive and extends longitudinally along said catheter body (10), coupled to said hollow needle (14) and to said source of R-F energy.
7. A catheter system according to any of claims 1 to 4 wherein said catheter body comprises a conductive tube, extending longitudinally along said catheter body, coupled to said hollow needle and to said source of R-F energy.
8. A catheter system according to any of claims 1 to 4 wherein said catheter body comprises a plastic tube, extending longitudinally along said catheter body, coupled to said hollow needle and to said fluid delivery means.
9. A catheter system according to any preceding claim, further comprising means for sensing electrical signals, coupled to said electrode surface.
10. A catheter system according to any preceding claim, further comprising means for delivering stim-

ulus pulses, coupled to said electrode surface.

11. An ablation catheter comprising:

an elongate catheter body (10) having a proximal portion, a distal portion and a longitudinal lumen;

a hollow needle (14) for penetrating body tissue at a desired location, mounted to a distal portion of said catheter body (10) and having an internal lumen coupled to the lumen of said catheter body (10); and

means (22) for coupling the internal lumen of the catheter body (10) to a source of conductive fluid, for delivering a conductive fluid to said lumen of the catheter body (10), characterised by

a conductive electrode surface (14) for delivering R-F energy to said desired location, mounted to said distal portion of said catheter body (10); and

means (24) for coupling a source of R-F electrical energy to said electrode surface (14), and wherein

said hollow needle is a helical needle.

Patentansprüche

1. Ablationskathetersystem mit

einem länglichen Katheterkörper (10), der einen proximalen Teil, einen distalen Teil und einen in Längsrichtung verlaufenden Hohlraum aufweist,

einer an einem distalen Teil des Katheterkörpers (10) montierten Hohnadel (14) zum Eindringen in Körpergewebe an einer gewünschten Stelle, mit einem mit dem Hohlraum des Katheterkörpers (10) gekoppelten inneren Hohlraum, und

einer mit dem inneren Hohlraum des Katheterkörpers gekoppelten Strömungsmittelquelle zur Abgabe eines leitenden Strömungsmittels an den besagten Hohlraum des Katheterkörpers (10),

gekennzeichnet durch

eine an dem distalen Teil des Katheterkörpers (10) montierte leitende Elektrodenfläche (14) zur Abgabe von HF-Energie an der gewünschten Stelle, und

eine mit der Elektrodenfläche (14) verbundene Quelle für elektrische HF-Energie, wobei die Hohnadel eine wendelförmige Nadel ist.

2. Kathetersystem nach Anspruch 1, wobei die Hohnadel leitend ist und die Elektrodenfläche eine Fläche der Hohnadel umfaßt.

3. Kathetersystem nach Anspruch 1 oder 2, wobei das Strömungsmittel-Abgabesystem eine Einrichtung zur Abgabe einer Ringer-Lösung aufweist.

4. Kathetersystem nach einem der vorhergehenden Ansprüche, wobei die Strömungsmittel-Abgabeeinrichtung einen das leitende Strömungsmittel enthaltenden Vorratsbehälter und eine Einrichtung zur Steuerung der Strömungsmittelströmung aufweist.

5. Kathetersystem nach einem der vorhergehenden Ansprüche, wobei der Katheterkörper ein in dessen Längsrichtung verlaufendes Drehmoment-Übertragungskabel aufweist.

6. Kathetersystem nach Anspruch 5, wobei das Drehmoment-Übertragungskabel leitend ist, in Längsrichtung des Katheterkörpers (10) verläuft und mit der Hohnadel (14) und der HF-Energiequelle gekoppelt ist.

7. Kathetersystem nach einem der Ansprüche 1 bis 4, wobei der Katheterkörper ein in dessen Längsrichtung verlaufendes leitendes Rohr aufweist, das mit der Hohnadel und der HF-Energiequelle gekoppelt ist.

8. Kathetersystem nach einem der Ansprüche 1 bis 4, wobei der Katheterkörper einen in dessen Längsrichtung verlaufenden Plastikschauch aufweist, der mit der Hohnadel und der Strömungsmittel-Abgabeeinrichtung gekoppelt ist.

9. Kathetersystem nach einem der vorhergehenden Ansprüche mit einer mit der Elektrodenfläche gekoppelten Einrichtung zur Erfassung elektrischer Signale.

10. Kathetersystem nach einem der vorhergehenden Ansprüche mit einer mit der Elektrodenfläche gekoppelten Einrichtung zur Abgabe von Stimulierungsimpulsen.

11. Ablationskatheter mit

einem länglichen Katheterkörper (10) mit einem proximalen Teil, einem distalen Teil und einem in Längsrichtung verlaufenden Hohlraum,

einer an einem distalen Teil des Katheterkörpers (10) montierten Hohnadel (14) zum Eindringen in Körpergewebe an einer gewünschten Stelle, mit einem mit dem Hohlraum des Katheterkörpers (10) gekoppelten inneren Hohlraum, und

einer Einrichtung (22) zum Anschluß des inneren Hohlraums des Katheterkörpers (10) an eine Strömungsmittelquelle zur Abgabe eines

leitenden Strömungsmittels an den Hohlraum des Katheterkörpers (10),
gekennzeichnet durch
eine an dem distalen Teil des Katheterkörpers (10) montierte leitende Elektrodenfläche (14) zur Abgabe von HF-Energie an der gewünschten Stelle, und
eine Einrichtung (24) zum Anschluß einer elektrischen HF-Energiequelle an die Elektrodenfläche (14),
wobei die Hohl-nadel eine wendelförmige Nadel ist.

Revendications

1. Système de cathéter d'ablation comprenant :

un corps de cathéter allongé (10) ayant une partie proximale, une partie distale et un lumen longitudinal ;
une canule (14) destinée à pénétrer dans un tissu corporel en un emplacement souhaité, monté sur une partie distale dudit corps de cathéter (10) et qui possède un lumen intérieur relié au lumen dudit corps de cathéter (10) ; et
une source de fluide conducteur reliée au lumen intérieur dudit corps de cathéter, et destinée à dispenser un fluide conducteur au dit lumen dudit corps de cathéter (10) ; caractérisé par
une surface d'électrode conductrice (14) destinée à fournir de l'énergie R-F au dit emplacement souhaité et montée sur ladite partie distale dudit corps de cathéter (10) ; et
une source d'énergie électrique R-F reliée à ladite surface d'électrode (14), et dans lequel ladite canule est une canule hélicoïdale.

2. Système de cathéter selon la revendication 1 dans lequel ladite canule est conductrice et dans lequel ladite électrode de surface comprend une surface de ladite canule.

3. Système de cathéter selon la revendication 1 ou la revendication 2, dans lequel ledit moyen permettant de dispenser le fluide conducteur comprend un moyen permettant de dispenser une solution Ringer.

4. Système de cathéter selon l'une quelconque des revendications précédentes dans lequel ledit moyen permettant de dispenser le fluide conducteur comprend un réservoir contenant ledit fluide conducteur et un moyen permettant de commander le débit du fluide.

5. Système de cathéter selon l'une quelconque des revendications précédentes dans lequel ledit corps

de cathéter comprend un câble de transfert de couple qui s'étend longitudinalement le long dudit corps de cathéter.

6. Système de cathéter selon la revendication 5 dans lequel ledit câble de transfert de couple est conducteur et s'étend longitudinalement le long dudit corps de cathéter (10) et est relié à ladite canule (14) et à ladite source d'énergie R-F.

7. Système de cathéter selon l'une quelconque des revendications 1 à 4 dans lequel ledit corps de cathéter comprend un tube conducteur qui s'étend longitudinalement le long dudit corps de cathéter, et est relié à ladite canule et à ladite source d'énergie R-F.



8. Système de cathéter selon l'une quelconque des revendications 1 à 4 dans lequel ledit corps de cathéter comprend un tube en plastique qui s'étend longitudinalement le long dudit corps de cathéter, et est relié à ladite canule et audit moyen permettant de dispenser le fluide.

9. Système de cathéter selon l'une quelconque des revendications précédentes comprenant en outre un moyen permettant de détecter des signaux électriques et qui est relié à ladite surface d'électrode.

10. Système de cathéter selon l'une quelconque des revendications précédentes comprenant en outre un moyen permettant de fournir des impulsions de stimulation et relié à ladite surface d'électrode.

11. Cathéter d'ablation comprenant :

un corps de cathéter allongé (10) ayant une partie proximale, une partie distale et un lumen longitudinal ;
une canule (14) destinée à pénétrer dans un tissu corporel en un emplacement souhaité, montée sur une partie distale dudit corps de cathéter (10) et qui possède un lumen intérieur relié au lumen dudit corps de cathéter (10) ; et
un moyen (22) permettant de relier le lumen intérieur du corps de cathéter (10) à une source de fluide conducteur, pour dispenser un fluide conducteur audit lumen du corps de cathéter (10), caractérisé par
une surface d'électrode conductrice (14) destinée à fournir de l'énergie R-F audit emplacement souhaité, qui est montée sur ladite partie distale dudit corps de cathéter (10) ; et
un moyen (24) permettant de relier une source d'énergie électrique R-F à ladite surface d'électrode (14), et dans lequel ladite canule est une canule hélicoïdale.






FIG. 3




FIG. 4




FIG. 5





FIG. 6



Europäisches Patentamt
European Patent Office
Office européen des brevets

(11) **EP 1 149 564 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
31.10.2001 Bulletin 2001/44

(51) Int. **A61B 18/14**
Cl. 7:

(21) Application number: **01119071.7**

(22) Date of filing: **28.07.1995**

(84) Designated Contracting States:
DE FR GB IT NL SE

(30) Priority: **08.09.1994 US 303246**

(62) Application number of the earlier
application in accordance with Art. 76
EPC: **95927486.1**

(71) Applicant: **Medtronic Inc.**
Minneapolis, MN 55432-5604 (US)

(72) Inventors:
, Mulier, Peter M. J.
St. Paul, Minnesota 55112 (US)

, Hoey, Michael F.
Shoreview, Minnesota 55126 (US)


(74) Representative:
Hughes, Andrea Michelle
Frank B. Dehn & Co.,
European Patent Attorneys,
179 Queen Victoria Street
London EC4V 4EL (GB)

Remarks:
This application was filed on 07 - 08 -
2001 as a divisional application to the
application mentioned under INID code
62.

(54) **Apparatus for R-F ablation**

(57) A method and apparatus for
ablation of body tissue. A catheter provided
with a hollow needle is employed both for
mapping the location to be ablated by
injection of an excitability reducing agent
and for ablating tissue, employing RF energy

in conjunction with an injected, conductive
fluid.



EP 1 149 564 A 1

Description

5 This invention relates generally to the field of devices for cardiac surgery, and more specifically to devices for R-F ablation of cardiac tissue.

The present invention is directed toward a device for treatment of tachyarrhythmias, which are heart rhythms in which a chamber or chambers of the heart exhibits an excessively fast rhythm. In particular, the present invention is directed toward a device for treatment of
10 tachycardias, which are due to the presence of ectopic foci within the cardiac tissue or due to the presence of aberrant conduction pathways within the cardiac tissue.

Therapies have been developed for treating tachycardias by destroying cardiac tissue containing identified ectopic foci or aberrant conduction pathways. A variety of approaches have
15 been taken, including application of electrical energy or other forms of energy to destroy the undesired cardiac tissue. As examples, ablation of cardiac tissue has been accomplished by means of radio frequency electrical current, microwave energy, heat, electrical pulses, cryotherapy, and lasers. At present, ablation using R-F energy is perhaps the most widely
20 practiced in the context of ablation procedures that can be carried out by means of a catheter, inserted into the closed heart.

Most R-F ablation catheters employ electrodes which are intended to contact the endocardium of the heart, or, as in U.S. Patent No. 5,083,565 to Parins, are intended to penetrate the
25 endocardium and enter the myocardium. In general, R-F ablation catheters are effective to induce small lesions in heart tissue including the endocardium and inner layers of myocardium, in the immediate vicinity of the electrode. However, the medical community has expressed a desire for devices which produce larger lesions, to reduce the number of applications of R-F energy
30 (burns) required to effectively ablate the cardiac tissue associated with the tachycardia.

R-F ablation causes tissue in contact with the electrode to heat as a result of resistance of the tissue to the induced electrical current therethrough. The actual extent of heating is
35 somewhat unpredictable. However, temperature tends to rise as the duration and amplitude of the R-F signal increase. Heating of the tissue beyond a certain point (i.e. 100 degrees C) can cause dissection or charring of the tissue, resulting in a high impedance between the R-F electrode and the return electrode, which in turn leads to cessation of the heating process, and,
40 in some cases, causes the electrode to stick to the charred tissue. One response to this phenomenon has been the inclusion of thermocouple within the ablation electrode, in conjunction with feedback control to modulate the R-F signal to maintain the electrode temperature at a set parameter. One such system is disclosed in U.S. Patent No. 5,122,137 to
45 Lennox et al.

The present invention is directed toward improving the consistency and efficacy of R-F ablation, by more accurately determining the ablation site and by increasing the overall size, extent and depth of the lesions induced by R-F ablation. These goals are pursued, according to
50 the invention, by means of an ablation catheter system, comprising:

an elongate catheter body having a proximal end, a distal end and having an internal lumen, open to the distal end of said catheter body;

55 a conductive electrode within said internal lumen;

EP 1 149 564 A1

a first conductor, coupled to said electrode;

means for coupling said conductor to a source of R-F energy; and

fluid delivery means coupled to said internal lumen of said catheter body for delivering a conductive fluid to said internal lumen; characterized by

a helical member extending from the distal end of said internal lumen.

The electrode is provided with a source of physiologic Ringer's solution, saturated Ringer's solution or other conductive fluid for injection into the tissue adjacent the electrode. In its preferred embodiment, the conductive solution is applied through apertures at the end of or along the length of the electrode. The conductive solution injected prior to application of the R-F signal is believed to displace blood and/or increase the amount of intracellular in the vicinity of the electrode. Ringer's solution, for example, has a much higher conductivity than blood (approximately 3-4x) or cardiac muscle (approximately 7x), overall resistance to the induced electrical current is reduced, which is believed to assist in expanding the size of the lesion, by spreading the effective area of application of the electrical current over a wider area. Application of the conductive solution during the burn can also increase the thermal conductivity of the tissue 30 - 50%, and further assists in expanding the size of the lesion by preventing overheating of the tissue, allowing for a prolonged application of the R-F signal, extending beyond the point at which burning or charring would otherwise normally occur. Injection of a saturated Ringer's or saline solution has an even more dramatic effect, and produces a 10 - 15 fold increase over the level of conductivity provided by physiologic Ringer's solution. All of these factors are believed to contribute to an increase in the overall size of the lesion produced by application of R-F energy at a particular location.

In some embodiments, the catheter is also provided with a second electrode, recessed within a lumen open to the distal end of the catheter. The open end of the lumen is held against heart tissue by the helical electrode, and the lumen is filled with a conductive fluid which serves to couple the recessed electrode to the tissue. The two electrodes may be used alone or in conjunction with one another to produce lesions of varying shape and location.

In some embodiments, the catheter is adapted to deliver a chilled or heated fluid, such as Ringer's solution, through the electrode, onto or into the tissue adjacent the electrode. Chilled fluid may be used to cool the tissue in a fashion similar to cryo-mapping as disclosed in U.S. Patent No. 5,281,213, issued to Milder et al. Typically, the temperature gradient provided by cryogenic cooling varies as a function of the thermal conductivity of the tissue, and the temperature gradient is typically quite steep. In the context of ablation of cardiac tissue, The ability to cool tissue deep in the ventricular wall has thus been limited by the requirement that the tissue adjacent the surface of the ventricular wall must not be cooled to the point of causing cellular damage. Injection of cooled fluid, such as Ringer's solution, serves to simultaneously cool the tissue and increase its thermal conductivity, with the net result that tissue deep in the ventricular wall can be cooled without cellular damage. In this context, directional injection of the chilled fluid through a laterally facing aperture in a hollow electrode, such as the opening at the distal end of a helical electrode, allows for

EP 1 149 564 A1

testing of multiple adjacent tissue locations by simply rotating the electrode in the tissue, without having to reposition the catheter. Subsequent directional delivery of conductive fluid may also be employed in conjunction with ablation of the tissue.

5 Heated Ringer's or other conductive fluid may be delivered through the electrode to further enhance the R-F ablation process. By raising the temperature of the solution to 50 degrees centigrade or less, conductivity increases of up to 200% in the fluid itself and corresponding conductivity increases of up to 30% in the tissue in which the fluid is injected, can be
10 achieved. Higher temperatures bring higher conductivities, and, for temperatures above 50 degrees centigrade, can cause ablation due to the heat of the delivered fluid as an adjunct to or a substitute for R-F ablation.

The catheters and electrodes disclosed are particularly optimized for ablation of heart
15 tissue. However, the benefits provided by the present invention are believed equally valuable in applications related to ablation of other tissue types, and in particular are believed valuable in ablation of tumors. It is expected that electrode sizes and shapes, the conductivities, volumes and flow rates of the injected fluids, and the parameters of the R-F signal applied to
20 the electrodes will vary as a function of the specific type of tissue being ablated.

Preferred embodiments of the invention will now be described, by way of example only, with reference to the accompanying drawings.

Figure 1 is a plan view of a catheter adapted to perform the improved method of R-F ablation,
25 according to the present invention.

Figure 2 is a cutaway view through the distal end of the catheter illustrated in Figure 1.

Figures 3 illustrates an alternative embodiment to the catheter of Figures 1 and 2, employing
30 a second, recessed electrode.

Figure 4 illustrates a cut-away view of the catheter of Figure 3, with its helical electrode located in heart tissue.

Figure 5 illustrates an ablation catheter adapted to deliver a chilled fluid to its helical
35 electrode, for mapping.

Figure 6 illustrates an ablation catheter adapted to deliver a chilled fluid to a porous, non-helical electrode, for mapping.

Figure 7 illustrates a second embodiment of an ablation catheter adapted to deliver a chilled
40 fluid to its helical electrode, for mapping, which also employs a recessed, second electrode.

Figure 8 illustrates a cut-away view through the distal portion of the catheter illustrated in Figure 5.

Figure 9 illustrates a cut-away view through the distal portion of the catheter illustrated
45 in Figure 6.

Figure 10 illustrates a cut-away view through the distal portion of the catheter illustrated in Figure 7.

Figure 11 illustrates a the distal portion of the catheter illustrated in Figure 5, with its
50 helical electrode located in heart tissue for directional mapping.

Figure 12 illustrates a pressurized source for Ringer's solution which may be employed in conjunction with the catheters in Figures 1 - 11.

Figure 1 is a plan view of a catheter specifically designed for performing R-F ablation
55 according to the present invention. The catheter includes an elongate catheter body 10, comprising an insulative outer sheath 12, which may be made of polyurethane, teflon, or other biocompatible plastic. A hollow, helical electrode 14 is located at the distal end of the

EP 1 149 564 A1

catheter and is coupled to the distal end of an internal tube, running the length of the catheter. At the proximal end of the catheter a fitting 16 is located, to which luer lock 18 is coupled. Luer lock 18 is coupled to the proximal end of the internal tube. A swivel mount 20 is mounted to luer lock 18, allowing rotation of the catheter relative to luer lock 22. Luer lock 22 is intended to be coupled to a source of conductive fluid such as Ringer's solution, and allows for application of the Ringer's solution through the catheter and through electrode 14, while electrode 14 is being screwed into heart tissue. An electrical connector 24 exits fitting 16, and is coupled to electrode 14, allowing for the use of electrode 14 to apply R-F energy to heart tissue. Electrode 14 may also be employed for other related functions such as measurement of electrograms within the heart and pacing of heart tissue by application of low energy pulses appropriate for cardiac pacing. In use, the catheter is advanced to the desired site for ablation, which preferably has been previously identified by means of cardiac mapping in a fashion similar to cardiac mapping presently employed with R-F ablation procedures. The catheter may be guided to the desired location by being passed down a steerable or guidable catheter, for example, as disclosed in U.S. Patent No. 5,030,204, issued to Badger et al., or by means of a fixed configuration guide catheter, for example in U.S. Patent No. 5,104,393, issued to Isner. Alternatively, the catheter may be advanced to the desired site within a heart by means of a deflectable stylet, as disclosed in PCT Patent Application WO 93/04724, published March 18, 1993, or a deflectable guidewire as disclosed in U.S. Patent No. 5,060,660, issued to Gambale, et al. When the hollow needle 14 is located at the desired location it is screwed into heart tissue by rotating the catheter body. A torque cable within the catheter body provides for 1:1 torque transfer from the proximal end of the catheter to the hollow needle 14.

When advanced to the desired location, luer lock 22 is coupled to a pressurized source of Ringer's or other conductive solution. An appropriate source is discussed in more detail in conjunction with Figure 6 below. However, for the purposes of the present invention, a source of Ringer's solution capable of delivering 2 cc per minute of solution at atmospheric pressure has been found to be adequate. Delivery of Ringer's solution should begin before or at the time at which the electrode 14 is screwed into the tissue to be ablated. In animal experimentation, the inventors have found that delivery of Ringer's solution for a period of five minutes prior to the delivery of R-F energy assists in producing a larger but still controlled, regular lesion.

After the electrode has been located, and Ringer's or other conductive solution has been administered for the desired period of time, electrical connector 24 is coupled to an R-F electrosurgical power source, of the type commercially available and employed for cutting, electro-coagulation or ablation. The present inventors have employed an Atakr Ablation System, manufactured by Cardiorhythm, San Jose, California, set to 50 watts output. At this setting, a prolonged application of R-F energy, e.g., for periods of two minutes, repeated immediately up to six times, may be employed to produce a large, controlled lesion. Greater or lesser time periods may be employed, however, time periods less than 20 seconds may be counter-indicated, as it appears that the cooling effect of the Ringer's solution, in such shorter R-F application times, may actually decrease the effective size of the lesion.

After R-F ablation, the electrode 14 may be coupled to a cardiac pacemaker, and cardiac pacing energy may be delivered to the lesion site in an attempt to measure the pacing threshold. Pacing threshold may be measured by delivering pacing pulses at differing energy levels, e.g. by altering pulse amplitude or width, and determining the minimum energy level effective to cause a depolarization of cardiac tissue. The inventors believe that the higher the pacing threshold,

EP 1 149 564 A1

assuming a relatively homogenous lesion, the greater lesion size. As such, the electrode 14 can be used to derive a rough estimate of overall lesion size. The electrode 14 may also be coupled to EKG monitoring equipment to assist in determining whether the tachycardia persists and whether the tissue in the vicinity of the electrode is still participating in aberrant conduction or ectopic activity, associated with the tachycardia.

The helical configuration of electrode 14 is believed to be particularly beneficial in the context of an ablation electrode. Because the electrode is screwed into and completely located within the heart tissue, out of the bloodstream, application of R-F energy is limited to the tissue itself. This differs from traditional R-F ablation electrodes, which simply contact the endocardium, with the result that a substantial portion of the energy applied is dissipated in the blood within the heart adjacent the electrode site. Moreover, R-F energy applied to the bloodstream may cause clotting of the blood adjacent the electrode, and raise the risk of clots breaking loose of the electrode.

The helical electrode also provides a substantially increased surface area as compared to the needle-like electrodes proposed in the above cited Parins patent, and also serves to anchor the catheter reliably during application of the R-F energy. In addition, the helical shape of the electrode prevents the application of conductive solution through the electrode from causing the electrode to be backed out of its insertion site due to hydraulic pressure, as might occur if a straight, hollow electrode were employed. The elongate path defined by the helical electrode also reduces the possibility of leakage of conductive fluid along the needle and out of the heart tissue.

Figure 2 illustrates a cutaway version through the end of the catheter illustrated in Figure 1. In this view, it can be seen that helical electrode 14 is provided with an internal lumen 26 which is in communication with the internal lumen of a tube 30. Tube 30 extends to the proximal end of the catheter and is in full communication with luer lock 18, as discussed above, tube 30 may be fabricated of polyamide tubing or of stainless steel tubing. In the present invention, the stainless steel tubing serves as an additional conductor, coupling electrode 14 to electrical connector 24 and enhancing the overall conductivity of the catheter. The use of polyamide tubing, while reducing the overall conductivity of the catheter enhances the flexibility somewhat, and may be beneficial in some cases. It is recommended to apply a steady flow of Ringer's solution through the tubing to electrode 14 during the passage of the catheter through the vascular system to the electrode site, if possible. The flow of Ringer's solution in this case assists in maintaining the patency of the lumen of tubing 30, and prevents plugging of the exit ports of the electrode as it is advanced into the cardiac muscle.

Surrounding tube 30 are two coils 32 and 34, which are wound in opposite directions, to provide a torque cable. In the case of the specific devices employed by the inventors, a torque cable as manufactured by Lake Region Manufacturing Company of Chaska, Minnesota was employed, which torque cable is described in U.S. Patent No. 5,165,421. Coils 32 and 34 also serve as conductors. As illustrated, tubing 30 is between metal coils 32 and 34 and helical electrode 14. However, if polyamide tubing is used, the coils 32 and 34 will serve as the only conductor and thus will be electrically coupled to electrode 14 by means of welding, soldering or mechanical interconnection. Insulative sleeve 12 serves both to provide a smooth exterior for the catheter and to insulate the metal coils 32 and 34, along the length of the catheter.

Electrode 14 comprises a hollow metal (e.g. stainless steel) tube, which may have only a single exit port 36, located as its distal end, or alternatively may be provided with a

EP 1 149 564 A1

plurality of ports 38, arranged around and along the length of electrode 14. If directional injection of fluid is desired, typically only port 36 will be present. If an even distribution of fluid is desired, ports 38 will be added to or substituted for port 36.

5 If desired, an insulative sleeve (not illustrated) which covers the proximal portion of the electrode may be provided, which serves to limit the application of R-F energy to the distal portion of the electrode. Exit ports 38 may be limited to the exposed, uninsulated portion of electrode 14, or may extend along the entire length of electrode 14. If desired, a thermocouple
10 or other temperature sensing device may be located within or attached to the electrode 14, to allow for temperature based feedback control of the R-F power applied to the electrode as described in the above-cited patent issued to Lennox et al.

15 Figure 3 illustrates a catheter employing a second, recessed electrode in addition to a penetrating, helical electrode 202 corresponding to electrode 14 as illustrated in Figure 1. Electrode 202 protrudes out of the distal end of the outer catheter sheath 200, which in turn is coupled to manifold 204, which includes a fluid fitting 206 and an electrical connector 208. Extending proximal to manifold 204 is a second manifold 210, preferably mounted rotatably with
20 regard to manifold 204, and carrying a second fluid coupling 212 and a second electrical connector 214. Electrical connector 214 is coupled to electrode 202, and corresponds to electrical connector 24 of the device illustrated in Figure 1. Fluid coupling 212 corresponds to luer lock 22 illustrated in Figure 1, and is employed to deliver Ringer's or other fluid to the
25 interior of electrode 202.

Figure 4 shows a cutaway view of the distal end of the catheter illustrated in Figure 3, with the electrode 202 screwed into heart tissue 224. In this view, it can be seen that within the outer catheter tube 200 is a second catheter body 218, which may correspond precisely to the
30 body of the catheter illustrated in Figure 1, and includes an internal lumen coupled to fluid connector 212 and to the interior of electrode 202, as well as an electrical conductor, for coupling electrode 202 to electrical connector 214.

35 Mounted within outer catheter tube 200 is an internal, recessed electrode 216 which is coupled to electrical connector 208 by means of an insulated conductor 220. In use, electrode 202 is screwed into heart tissue 224, holding the distal end of outer catheter tube 200 tightly adjacent the tissue. Lumen 222 may then be filled with Ringer's solution, providing a conductive connection between the ring electrode 216 and the heart tissue 224. Electrodes 216 and 202
40 may be used individually or in conjunction with one another, to control the depth and shape of the lesion provided.

45 A typical lesion outline for the helical electrode 202 is illustrated by the broken line at A, while a typical lesion outline for the recessed electrode 216 is illustrated at the broken out line at B. The lesions produced by recessed electrode 216 tend to be conically shaped, and located more closely adjacent the surface of the tissue. The lesions produced by electrode 202 tend to be more spherical or ovoid in configuration, and tend to be located deeper within the
50 tissue.

55 Figure 5 illustrates an embodiment of a catheter particularly adapted for use in delivery of a chilled or a heated fluid through its helical electrode 302, to accomplish cardiac mapping, prior to ablation or to enhance conductivity during ablation, respectively. The catheter is provided with an elongate outer catheter tube 300, which terminates in a molded plastic member 304, from which the helical electrode 302 emerges. At its proximal end, a manifold 306 is coupled to outer catheter tube 300 and is provided with fluid couplings 308 and 310, for the

EP 1 149 564 A1

ingress and egress, respectively, of a cooling or heating fluid. Manifold 306 is also provided with an electrical connector 312 which is coupled electrically to helical electrode 302 and with a fluid coupling 314 which is coupled to the interior of electrode 302, and is used to deliver
5 Ringer solution through electrode 302.

A cutaway view through the distal portion of the catheter illustrated in Figure 5 is shown in Figure 8. In this view, it can be seen that located within the outer catheter tube are an inner catheter tube 306 and a metal tube 308, fabricated, for example of a stainless hypodermic tube,
10 which serves to electrically couple electrode 302 to electrical connector 312 and to provide a fluid pathway from fluid coupling 314 to the interior of electrode 302. Plastic member 304 seals the distal end of the catheter body to the electrode 302.

The inventors have determined that it is difficult to inject chilled or heated fluids down the length of the catheter as illustrated in Figure 1 and Figure 2, without the chilled or heated solution approaching body temperature by the time it reaches the helical electrode. As a result, as illustrated in Figure 8, the inventors have derived a catheter which provides for three fluid flow channels, arranged concentrically. The inner channel, defined by the hypotubing 308 serves to deliver the fluid to be heated or cooled(e.g. Ringer's solution) to the tissue, through electrode 302. The second fluid pathway, defined by the space between the inner tubing 306 and the hypotubing 308, is coupled to fluid coupling 310, which in turn is to be coupled to a pumping means for pumping chilled or heated saline or other fluid down the catheter body, through this intermediate lumen, in order to keep the Ringer's solution within hypotube 308 in a chilled or heated state. At the distal end of the catheter, the cooling fluid leaves the intermediate lumen and enters the outer lumen defined by the space between outer catheter tube 300 and inner catheter tube 306, where it travels back up the catheter proximally, to fluid coupling 308, for recirculation or disposal. A pressurized source for Ringer's solution to be injected into the tissue is illustrated in Figure 12, and would be coupled to fluid fitting 314, illustrated in Figure 5. Any appropriate pumping mechanism may be used to deliver heating or cooling fluid to fluid coupling 310 and to remove it from fluid coupling 308.
25

For purposes of mapping, it is preferred that the fluid delivered to the helical electrode 302 and injected into the tissue be no more than 5°C. In order to accomplish this, the temperature of the coolant fluid applied to fluid coupling 310 should be adjusted. If desired, a thermocouple, as discussed above, might optionally be employed in conjunction with electrode 302, and employed for temperature controlled regulation of the coolant temperature, as well as for temperature based feedback regulation of RF power applied to the electrode ablation.
40

Tissue mapping using the catheter of Figure 5 is accomplished by screwing the electrode 302 into the tissue to be tested, followed by delivery of chilled Ringer's solution at 5°C or less, in order to slow conduction through the tissue, and monitoring the electrical activity of the heart by means of electrode 302, through electrical connector 312 (Fig. 5), while the patient is undergoing an episode of spontaneous or induced tachyarrhythmia. If cooling of the tissue terminates the arrhythmia, the site is identified as an appropriate location for RF ablation.
50

If the electrode 302 is provided with only a single aperture, or with apertures directed only in a single direction, the catheter may be used to map multiple adjacent tissue sites, as illustrated in Figure 11.

Figure 11 shows the distal end of the catheter illustrated in Figure 8, screwed into heart tissue. As illustrated at broken-out line C, chilled saline is injected through the aperture at the distal end of the helix tends to enter the tissue in a single direction. By rotating the
55

EP 1 149 564 A1

helix, while in the tissue, multiple adjacent tissue sites may be sequentially mapped, without the necessity of removing the catheter from the tissue. RF energy may subsequently be applied, along with directional injection of Ringers, in order to ablate the identified arrhythmogenic tissue.

5 Figure 9 illustrates an alternative version of a mapping/ablation catheter differing from that illustrated in Figure 8 primarily in that rather than a helical electrode 302 (Fig. 8), a porous electrode 402 is provided, mounted to the distal end of the outer catheter tube 400. Porous electrode 402 is preferably fabricated by powder metallurgy techniques, similar to those
10 described in conjunction with United States Patent No. 4,506,680, issued to Stokes, and is provided with a porosity which provides a high resistance to fluid flow, for example no more than X cc's of fluid per minute at a pressure of Y N/M². Electrode 402 is coupled electrically to electrical connector 412 and is coupled to a length of hypotubing within outer catheter body 400,
15 which is in turn coupled to fluid coupling 414. Fluid couplings 410 and 408, on manifold 406 correspond to fluid couplings 308 and 310, mounted on manifold 306, in Figure 5.

Figure 9 shows a cutaway version through the distal portion of the catheter illustrated in Figure 6, and in this view it can be seen that its internal structure is similar to that of the
20 catheter illustrated in Figure 8. A length of hypotubing 408 is coupled to electrode 402, providing both a fluid pathway to the electrode and an electrical connection to the electrode. Coolant enters the catheter through fitting 410, and flows down the catheter between inner catheter tube 306 and hypotube 408. Coolant exits the catheter flooding proximally between outer
25 catheter tube 400 and inner catheter tube 406. In the context of the present invention, the provision of a porous electrode 402 having a high resistance to fluid flow prevents the delivered chilled fluid from simply leaking out and being washed away in the blood stream. By restricting the flow through the electrode, the electrode can be cooled to a degree which will
30 allow its use for mapping purposes. The catheter may also be employed for ablation, with delivery of Ringer's solution or other fluid through hypotube 408 being employed primarily to prevent overheating of electrode 402. As in conjunction with the embodiments of the present invention employing helical electrodes, electrode 402 might also optionally be provided with a
35 thermocouple, allowing for temperature control feedback of electrode temperatures during both mapping and ablation.

Figure 7 illustrates a second embodiment of a catheter, employing features of the catheters illustrated in Figures 3 and 5, in a single device. Outer catheter tube 500 carries a manifold
40 506 at its proximal end, which includes fluid couplings 508 and 510, for egress and ingress, respectively, of cooling or heating fluid. Electrical connector 512 is coupled to helical electrode 502. Fluid coupling 514 is coupled to the interior of electrode 502, allowing for delivery of Ringer's solution to the tissue, through electrode 502. Electrical connector 516
45 corresponds functionally to electrical connector 208 in Figure 3, and is coupled to a recessed electrode located within outer catheter tube 500. Fluid coupling 518 corresponds functionally to fluid coupling 206 illustrated in Figure 3, and serves to allow delivery of Ringer's solution within the outer catheter tube 500, in order to couple the recessed electrode tube, in the same
50 fashion as discussed in conjunction with Figure 4, above.

Figure 10 is a cutaway view through the distal end of the catheter illustrated in Figure 7. In this version of the invention, the catheter defines four concentric fluid paths. The innermost fluid path is defined by hypotubing 524 which is coupled to helical electrode 502.
55 Ringer's solution is delivered from fluid coupling 514, through tube 524 to electrode 502. Tube 524 also is coupled to electrical connector 512. Mounted around tube 524 is inner catheter tube

EP 1 149 564 A1

526, which corresponds functionally to inner catheter tubes 306 and 406 as illustrated in Figures 8 and 9, respectively. Cooling or heating fluid flows distally through the catheter in the fluid space defined between inner catheter tube 526 and hypotube 524. Intermediate catheter tube 522 surrounds inner catheter tube 526, and the space there between defines the return fluid flow path for coolant fluid, which is in turn coupled to fluid coupling 508. Plastic number 504 corresponds to plastic number 304 in Figure 8, and serves to seal the distal end of intermediate catheter tube 522. A ring electrode 520 is mounted around plastic number 502 and is coupled to electrical connector 516 by means of insulative conductor 528. The space between outer catheter tube 500 and intermediate catheter tube 522 defines the fourth, concentric fluid flow path, and is coupled to fluid coupling 518, allowing for injection of Ringer's solution into the interior of outer catheter tube 500, which in turn serves to couple electrode 520 to cardiac tissue, in the same fashion as discussed in conjunction with the catheter illustrated in Figures 3 and 4.

After mapping, and after the tissue has warmed, ablation may be accomplished in the same fashion as discussed above in conjunction with the catheter illustrated in Figures 1 and 2. Alternatively, the catheters of Figures 5 and 7 may be employed to deliver heated Ringer's solution through the helical electrodes to further enhance conductivity. As noted above, heated Ringer's solution displays an increased conductivity as compared to body temperature fluid. In addition, with fluid temperatures of 50 degrees C or above, the heated fluid itself serves to ablate tissue, even in the absence of R-F energy. Any appropriate commercially available heating or cooling bath may be employed to regulate the temperature of the applied solution.

Figure 12 illustrates a pressurized source for Ringer's or saline solution which may be employed to deliver solution to the electrodes of the catheters described above. A reservoir 100 is provided, which is commercially manufactured by Block Medical Inc., and sold under the brand name "Home Pump". The reservoir contains Ringer's solution or other conductive fluid and provides the fluid at one atmosphere pressure to flow control 102, via filter 104. Flow control 102 may, for example, provide a flow limit of 40 drops or 2 cc per minute. Flow control 102 is coupled to a second flow control element 104, which, in the experimental apparatus employed by the inventors allows for additional adjustability of flow rates. Flow control 102 or 104 preferably includes a one-way valve, providing a fluid column which prevents tissue from entering and plugging of the holes in the electrode. Flow control 104 is coupled to the luer lock 22, illustrated in Figure 1, which in turn is in fluid communication with electrode 14 (Figure 1), allowing delivery of Ringer's solution to the electrode. An electrosurgical generator 200 for providing R-F electrical energy is illustrated in functional block form, coupled to electrical connector 24 and to a ground plate electrode 202 (not drawn to scale). All other labeled elements correspond to those illustrated in Figure 1.



While the embodiment illustrated above requires a second element (e.g. a guide catheter or guide wire) for advancing and positioning the catheter at its desired location, it is anticipated that the basic apparatus disclosed above may also be incorporated into catheters which themselves are steerable or deflectable, similar to R-F ablation catheters presently in clinical investigation. Similarly, it is anticipated that in commercial embodiments, alternative mechanisms (e.g. precision pumps) for controlling the flow of Ringer's solution may be employed. Similarly, while the inventors have employed Ringer's solution, other alternative fluids may be workable as well. As such, the embodiment discussed above should be considered exemplary, rather than limiting, in conjunction with the following claims.

EP 1 149 564 A1

Claims

- 5 1. An ablation catheter system, comprising:
- an elongate catheter body (12) having a proximal end, a distal end and having an internal lumen, open to the distal end of said catheter body;
- 10 a conductive electrode (402) within said internal lumen;
- a first conductor (16), coupled to said electrode;
- 15 means (24) for coupling said conductor (16) to a source of R-F energy; and
- fluid delivery means (22) coupled to said internal lumen of said catheter body for delivering a conductive fluid to said internal lumen; **characterized by**
- 20 a helical member (14) extending from the distal end of said internal lumen.
- 25 2. An ablation catheter system according to claim 1, wherein said helical member is conductive and further comprising a second electrical conductor coupled to said helical member.
- 30 3. An ablation catheter system according to claim 2, wherein said helical member is hollow and further comprising means for delivering a conductive fluid to said helical member.
- 35 4. An ablation catheter system according to claim 1, 2 or 3, further comprising a source of R-F energy, coupled to said first conductor.








FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. II




FIG. 12

EP 1 149 564 A1



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 11 9071

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
P, A	US 5 431 649 A (HOEY MICHAEL F ET AL) 11 July 1995 (1995-07-11) * abstract *	1	A61B17/39
A	US 5 342 357 A (NARDELLA PAUL C) 30 August 1994 (1994-08-30) * abstract *	1	
A	US 4 682 596 A (SMITH KEVIN W ET AL) 28 July 1987 (1987-07-28) * abstract *	1	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7) A61B
Place of search THE HAGUE		Date of completion of the search 5 September 2001	Examiner Papone, F
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application I : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 02 (P04C01)

EP 1 149 564 A1

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 01 11 9071

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

05-09-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5431649 A	11-07-1995	AU 676630 B	13-03-1997
		AU 1427995 A	21-03-1995
		CA 2168860 A	02-03-1995
		DE 69419038 D	15-07-1999
		DE 69419038 T	25-05-2000
		EP 0774926 A	28-05-1997
		JP 2761440 B	04-06-1998
		JP 9500810 T	28-01-1997
		US 5980516 A	09-11-1999
		WO 9505781 A	02-03-1995
		US 5807395 A	15-09-1998
		US 6016809 A	25-01-2000
US 5342357 A	30-08-1994	AU 5544894 A	08-06-1994
		EP 0746250 A	11-12-1996
		WO 9410925 A	26-05-1994
		US 5437662 A	01-08-1995
US 4682596 A	28-07-1987	US RE33925 E	12-05-1992

EPC FORM P449

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82